



# Clearance certificate

## for conversion of the handlebar / stem combination with a 25,4 mm clamping diameter

Wilhelm Humpert GmbH & Co. KG hereby confirms that for the bicycle categories listed below it has no reservations about the use of the following handlebar/stem combination with "Safety Level 5".

- **Single- and multi-track transportation- and cargo bikes** with motorised pedal assistance up to a **speed of 25 km/h** and a maximum **permissible total weight of 250 kg**

The combinations have been sufficiently tested and meet the requirements of the "DIN 79010:2020" standard. A risk analysis has also been carried out. No hazard is therefore to be expected in connection with use on a bicycle in its original condition. However, the prerequisite for this is that the length of the brake and gear cables and/or lines has not been changed and that the bicycle remains in the prescribed condition.


Handlebar		Stem	
Art. No.	Sales designation	Art. No.	Sales designation
16212101	ergotec „ERGO XS/25,4“ / AL 6061 T6	40125001; 40125101	ergotec „CHARISMA25,4“ / AL 6061 T6
16198101	ergotec „ERGO S/25,4“ / AL 6061 T6	40126001; 40126101	
16200101	ergotec „ERGO M/25,4“ / AL 6061 T6		
16202101	ergotec „ERGO L/25,4“ / AL 6061 T6	40130001; 40130101	ergotec „HIGH CHARISMA/25,4“ / AL 6061 T6
16227101	ergotec „ERGO XL/25,4“ / AL 6061 T6	40135001; 40135101	
16229101	ergotec „ERGO XXL/25,4“ / AL 6061 T6		
		40272001; 40293001	ergotec „COVER/25,4“ / AL 6061 T6

**Please note:** the last digit "1" refers to the packaging and is "0" in the case of OEM products.

**This certificate must be handed over to the customer after the conversion.**

Wilhelm Humpert GmbH & Co. KG

  
 Steve Richter, M.A.  
 Test engineer - Testcenter

  
 Rolf G. Häcker  
 Head of Product Development  
 Member of the Certification  
 Committee

Valid as an original document with the coloured Humpert header and footer, or as a certified copy.

As a bicycle retailer I hereby confirm that this copy is a true representation of the original:

\_\_\_\_\_  
Stamp/signature